

## Specifications 911 Targa 4 / 911 Targa 4S\*

<b>Body:</b>	Monocoque; lightweight all-steel bodyshell, hot-galvanised on both sides; full-size frontal, side and head airbags for the driver and front passenger; 2+2-seater.
<b>Aerodynamics:</b>	Drag coefficient $C_d = 0.30$ (Targa 4S: 0.29) Frontal area $A = 2.04 \text{ m}^2$ $C_d \times A = 0.61$ (Targa 4S: 0.59)
<b>Power Unit:</b>	Six-cylinder aluminium horizontally-opposed water-cooled engine; engine block and cylinder heads made of aluminium; four overhead camshafts; four valves per cylinder; adjustment of valve timing on the intake camshaft and modification of valve lift (VarioCam Plus); hydraulic valve play compensation; switching intake manifold; integrated dry sump lubrication; two-stage catalyst system left and right; two pre- and two after-catalyst oxygen sensors; secondary air system; engine oil 10.3 litres (2.27 Imp gals); coolant 31 litres (6.82 Imp gals); DME Digital Motor Electronic engine management for ignition, fuel injection and camshaft adjustment; electronic solid-state ignition (six ignition coils); sequential multipoint fuel injection.
<b>Bore:</b>	96 mm/3.78" (Targa 4); 99 mm/3.90" (Targa 4S)
<b>Stroke:</b>	82.8 mm/3.26"
<b>Capacity:</b>	3596 cc (Targa 4); 3824 cc (Targa 4S)
<b>Compression Ratio:</b>	11.3:1 (Targa 4); 11.8:1 (Targa 4S)
<b>Max Output:</b>	239 kW/325 bhp at 6800 rpm (Targa 4); 261 kW/355 bhp at 6600 rpm (Targa 4S)
<b>Max Torque:</b>	370 Nm (273 lb-ft) at 4250 rpm (Targa 4); 400 Nm (295 lb-ft) at 4600 rpm (Targa 4S)
<b>Output per litre:</b>	66.5 kW/90.4 bhp (Targa 4); 68.3 kW/92.9 bhp (Targa 4S)
<b>Max Engine Speed:</b>	7300 rpm
<b>Fuel Grade:</b>	Premium plus (RON/MON 98/88), unleaded
<b>Electrical System:</b>	12 V, 2100 W alternator, 70 Ah battery capacity

\* Specifications may vary in accordance with national regulations

**Power Transmission:** Power unit and transmission bolted together to form one unit; drive power conveyed by double propeller shafts to the rear wheels and via a driveshaft and viscous multiple-plate coupling to the front wheels.

Gear ratios:	Manual	Tiptronic S
1 <sup>st</sup>	3.91	3.60
2 <sup>nd</sup>	2.32	2.19
3 <sup>rd</sup>	1.61	1.41
4 <sup>th</sup>	1.28	1.00
5 <sup>th</sup>	1.08	0.83
6 <sup>th</sup>	0.88	–
Reverse	3.59	3.17
Final drive:		
Rear axle	3.44	3.56
Front axle	3.33	3.45

Clutch diameter: 240 mm (9.45")  
(self-adjusting on the Targa 4S)

**Chassis and Suspension:** Front axle: Spring strut configuration (optimised by Porsche) with spring strut-guide independent suspension on track control and longitudinal arms; cone stump springs with inner-mounted dampers; twin-sleeve gas pressure dampers (with active control on the Targa 4S).

Rear axle: multi-arm configuration; independent wheel suspension on five track control arms; cylindrical coil springs on each wheel with coaxial, inner-mounted dampers; single-sleeve gas pressure dampers (with active control on the Targa 4S).

**Brakes:** Two-circuit brake system split front-to-rear; four-piston aluminium monobloc brake callipers; cross-drilled, inner-vented brake discs on the front axle measuring 318 x 28 mm (12.52 x 1.10") diameter/width on the Targa 4 and 330 x 34 mm (13.00 x 1.38") diameter/width on the Targa 4S, and at the rear 299 x 24 mm (11.78 x 0.95") diameter/width on the Targa 4 and 330 x 28 mm (13.00 x 1.10") on the Targa 4S; PSM 8.0; vacuum brake servo.

<b>Wheels and Tyres:</b>	front	8 J x 18	on	235/40 ZR 18 (Targa 4);
		8 J x 19	on	235/35 ZR 19 (Targa 4S)
	rear	11 J x 18	on	295/35 ZR 18 (Targa 4);
		11 J x 19	on	305/30 ZR 19 (Targa 4S)

<b>Weight:</b>	DIN, unladen	1510 kg (Targa 4 manual) 1550 kg (Targa 4 with Tiptronic S) 1535 kg (Targa 4S manual) 1575 kg (Targa 4S with Tiptronic S)
	Max permissible	1900 kg (Targa 4 manual) 1945 kg (Targa 4 with Tiptronic S) 1915 kg (Targa 4S manual) 1960 kg (Targa 4S with Tiptronic S)

<b>Dimensions:</b>	Length	4427 mm (174.3")
	Width	1852 mm (72.9")
	Height	1310 mm (51.6") (Targa 4) 1300 mm (51.2") (Targa 4S)
	Wheelbase	2350 mm (92.5")
	Track	front 1488 mm (58.6") rear 1548 mm (60.9")

Luggage compartment capacity  
to VDA standard: 105 litres (3.68 cu ft), overall  
Fuel tank: 67 litres (14.75 Imp gals)



**Fuel consumption, Targa 4\***

<b>(EU standard):</b>	Urban	16.6 (17.4) litres
	Extra-urban	8.4 (8.6) litres
	Composite	11.3 (11.6) litres

**Fuel consumption Targa 4S\***

<b>(EU standard):</b>	Urban	17.5 (18.0) litres
	Extra-urban	8.5 (8.6) litres
	Composite	11.8 (11.9) litres

**CO<sub>2</sub> emissions Targa 4\***

<b>(EU standard):</b>	272 (280) g/km
-----------------------	----------------

**CO<sub>2</sub> emissions Targa 4S\***

<b>(EU standard):</b>	285 (286) g/km
-----------------------	----------------

\*Figures in brackets relate to cars with Tiptronic S